# N 90 C17FS32H0B **COMPACT STEAM OVEN**





Compact built-in oven with FullSteam - combining all heating types and steam cooking in a single oven in a very small space

- $\sqrt{\ }$  The new FullSteam® oven combines CircoTherm® oven and steam cooker in a single unit.
- $\sqrt{\,}$  Shift Control fast navigation through menus and simple operation with the generous TFT display.
- $\sqrt{\mbox{ EcoClean}}$  the self-cleaning catalytic coating on the inside top and sides of the oven makes oven cleaning easier.

- $\sqrt{\ }$  BaseClean the special cleaning programme for the oven floor.
- $\sqrt{\text{Modern LED lighting for bright, even illumination}}$
- $\sqrt{\phantom{.}}$  Home Connect rediscover your kitchen with our connected home appliances, from wherever you are.



















## Optional accessories

Z11SZ60X0 SeamlessCombination 45 + 14cm Z11SZ90X0 SeamlessCombination 60 + 45cm Z12CB10A0 Baking tray, anthracite enamelled Z12CM10A0 Moussaka pan, anthracite enamelled Z12CQ10A0 Grill tray, anthracite enamelled

Z13CV06S0 Decor strip

Z13TC10X0 ComfortFlex Rail (1 level) f. steam Z1665X0 porcelain tray-GN1/3- unpunched porcelain tray-GN2/3- unpunched 71685X0

Z18F45X0 Cookbook

#### Technical Data

Color / Material Front : Stainless steel Built-in / Free-standing : Built-in Door opening: Drop down

Required niche size for installation (HxWxD) :  $450-455 \times 560-568 \times 10^{-2}$ 

Dimensions of the product (mm) :  $455 \times 596 \times 548$ 

Dimensions of the packed product (HxWxD) (mm) :  $540 \times 660 \times 690$ 

Control Panel Material: Stainless steel

Door Material : Glass Net weight (kg): 34.105 Approval certificates : CE, VDE

Length electrical supply cord (cm): 150

EAN code: 4242004236108

Current (A): 16 Voltage (V): 220-240 Frequency (Hz): 60; 50 Plug type: no plug

Approval certificates : CE, VDE Number of cavities (2010/30/EC): 1

Usable volume (of cavity) - NEW (2010/30/EC) : 47

Energy efficiency class (2010/30/EC): A+

Energy consumption per cycle conventional (2010/30/EC) : 0.73 Energy consumption per cycle forced air convection (2010/30/EC):

Energy efficiency index (2010/30/EC): 81.3



# N 90 C17FS32H0B COMPACT STEAM OVEN

#### Features

#### Design

- 4.1" TFT colour and graphics display with ShiftControl
- Illuminated Shift Control
- Cavity inner surface: Enamel anthracite
- Drop down door, SoftClose, soft opening
- Bar handle

#### **Features**

- HomeConnect ready on WLAN
- Control panel lock
   Automatic safety switch off
   Residual heat indicator

Start button

Door contact switch

- Temperature proposal Actual temperature display Heating up indicator Sabbath setting
- Baking and roasting assistant, Automatic programmes
- LED light
- Water tank empty indicator
- Triple glazed door

#### Cleaning

- $\bullet$  EcoCleanDirect : ceiling, back panel, side liners
- EcoClean programme, Base Clean programme
- De-scaling programme
- Full glass inner door

### Programmes/functions

- 12 heating methods: CircoTherm®, CircoTherm® Gentle, Top/bottom heat, Conventional heat Gentle, Hot air grilling, Full surface grill, Centre surface grill, CircoTherm® intensive, Bread baking, Bottom heat, Low temperature cooking, Keep warm
- Additional heating methods with steam: Steaming, Reheat, Dough proving, Defrost
- Additional functions:

De-scaling programme

Drying function

Automatic boiling point detection

- Number of automatic programmes: 30 PC
- Rapid heat
- Cooling fan

### Accessories

- Available as an accessory
- 1 x steam container, punched, size S, 1 x steam container, punched, size XL, 1 x steam container, unpunched, size S, 1 x grid, 1 x universal pan

#### Performance/technical information


• Energy efficiency rating (acc. EU Nr. 65/2014): A+ Energy consumption per cycle in conventional mode: 0.73 kwh Energy consumption per cycle in fan-forced convection mode: 0.61 kwh

Number of cavities: Main cavity Heat source: electrical Cavity volume: 47 litre


- 1 I Water tank capacity
- Location of the steam generator is outside of the cavity
- Total connected load electric: 3.3 KW
  Temperature range 40 °C 250 °C
- Length of mains cable: 150 cm
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 455 mm x 596 mm x 548 mm
- Niche dimension (hxwxd): 450 mm 455 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual

# N 90 C17FS32H0B COMPACT STEAM OVEN

## Dimensioned drawings



Installation with a hob.



measurements in mm

If the compact appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	42 mm	43 mm
Full surface Induction hob	52 mm	53 mm
Gas hob	32 mm	43 mm
Electric hob	32 mm	35 mm