


N 70
OVEN WITH VARIOSTEAM
B57VR22N0B



COOKING PASSION SINCE 1877



A+



Built-in oven with VarioSteam® and SLIDE&HIDE® - fuller flavour and unrestricted access to the oven interior.

- ✓ Slide&Hide® - the fully retracting oven door.
- ✓ VarioSteam® - Steam assistance for CircoTherm® ovens, that cooks foods moist on the inside and crisp on the outside.
- ✓ The duo for perfect cleaning: Pyrolysis after heavy use - the oven interior cleans itself.
- ✓ EasyClean® - the environment-saving option for fast oven cleaning.
- ✓ ShiftControl - fast navigation through menus and simple operation with the TFT display.
- ✓ Modern LED lighting for bright, even illumination.

Features

Technical Data

Color / Material Front : Stainless steel
Built-in / Free-standing : Built-in
Integrated Cleaning system : Hydrolytic, Pyrolytic
Required niche size for installation (HxWxD) : 585-595 x 560-568 x 550
Dimensions of the product (mm) : 595 x 596 x 548
Dimensions of the packed product (HxWxD) (mm) : 675 x 690 x 660
Control Panel Material : Stainless steel
Door Material : Glass
Net weight (kg) : 43.3
Usable volume of cavity (l) : 71
Cooking method : , Bottom heat, Bread Baking Setting, Conventional heat, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, low temperature cooking, Pizza setting, warming
First cavity material : Enamelled
Number of interior lights : 1
Approval certificates : CE, VDE
Length electrical supply cord (cm) : 120
Interior Lights - cavity 1 : 1
Pull-out system : Accessory
Clock function : Alarm, Off, On
Included accessories cavity 1 : 2 x combination grid, 1 x universal pan
Broil Element Wattages cavity 1 (W) : 2800
Convection Element Wattages cavity 1 (W) : 2300
Energy efficiency class (2010/30/EC) : A+
Energy consumption per cycle conventional (2010/30/EC) : 0.87
Energy consumption per cycle forced air convection (2010/30/EC) : 0.69
Energy efficiency index (2010/30/EC) : 81.2
Electrical connection rating (W) : 3450
Current (A) : 16
Voltage (V) : 220-240
Frequency (Hz) : 60; 50
Plug type : no plug
Color / Material Front : Stainless steel
Energy input : Electric
Approval certificates : CE, VDE
Required cutout/niche size for installation (in) : x x
Dimensions of the packed product (in) : 26.57 x 25.98 x 27.16
Net weight (lbs) : 95
Gross weight (lbs) : 100
Length electrical supply cord (cm) : 120
Net weight (kg) : 43.3
Gross weight (kg) : 46.0

Included accessories

2 x combination grid, 1 x universal pan

Optional accessories

Z11CG10X0 : Accessory , Z11CR10X0 : Baking and roasting grid (standard) , Z11GT10X3 : Glass roasting dish, 5,4l , Z11GU20X0 : Glasspan , Z11SZ00X0 : SeamlessCombination mounting kit , Z11SZ80X0 : SeamlessCombination 60 + 29cm , Z11SZ90X0 : SeamlessCombination 60 + 45cm , Z11TC10X0 : ComfortFlex Rail (1 level) , Z11TC16X0 : ComfortFlex Rail (1 level) , Z12CB10A0 : Baking tray, anthracite enamelled , Z12CL10A0 : Lid for professional pan, enamelled anth , Z12CM10A0 : Moussaka pan, anthracite enamelled , Z12CN10A0 : Professional pan, anthracite enamelled , Z12CP10A0 : Pizza pan, anthracite enamelled , Z12CQ10A0 : Grill tray, anthracite enamelled , Z12CU10A0 : Multipurpose pan, anthracite enamelled , Z12TF36X0 : 3 level telescopic rails, full ext,pyro , Z13CV05S0 : Cover Strip , Z18V60X0 : Cookbook , Z1913X0 : Baking Stone , Z19DD10X0 : Steam set for ovens , Z9220W0 : Conversion cabinet , Z99RX70X0 : Connecting cable 3m



N 70

OVEN WITH VARIOSTEAM

B57VR22NOB

Features

Heating Functions

- Oven with 12 heating methods:
 - CircoTherm®
 - CircoTherm® Eco
 - Top/bottom heating
 - Top/bottom heating Eco
 - Circo-roasting
 - Full surface grill
 - Centre area grill
 - CircoTherm® Intensive
 - Bread Baking
 - Bottom heating
 - Low temperature cooking
 - Keep warm
- Additional heating methods with steam: Reheating, Dough Proving
- Temperature range 40 °C - 275 °C
- Cavity volume: 71 net usable litres

Design

- Illuminated ShiftControl
- Anthracite enamel cavity with 4 shelf positions

Cleaning

- Pyrolytic self cleaning
- EasyClean® Cleaning aid programm
- Full glass inner door - safer touch door

Convenience

- 2.5" colour and text Display with ShiftControl
- Temperature proposal
 - Optical temperature control
 - Actual temperature display
 - Sabbath setting
- Additional functions:
 - Descaling program
 - Steam cooking function (system steamer accessory required)
 - Drying function
- Slide&Hide® door, SoftOpen
- Automatic programs
- Number of automatic programmes: 14 PC
- Electronic clock
- Rapid heating-up
- LED lighting
- Large 1 litre water tank
- Water tank empty indicator
- Location of the steam generator is outside of the cavity
- Cooling fan
- Stainless-steel fan
- Info button
- Revolution handle

Hook-in racks / rails

- Cavity with shelf support rails, Telescopic slide-out Accessory

Accessories

- 2 x combination grid, 1 x universal pan

Safety and Environment

- Individual adjustable child lock
 - Safety switch off
 - Residual heat indicator
 - start button
 - Door contact switch


Technical Info

- Length of mains cable: 120 cm
- Total connected load electric: 3.45 KW
- Appliance dimensions (HxWxD): 595 mm x 596 mm x 548 mm
- Installation dimensions (HxWxD): 585 mm - 595 mm x 560 mm - 568 mm x 550 mm
- Please reference the built-in dimensions provided in the installation drawing
-

N 70
OVEN WITH VARIOSTEAM
B57VR22NOB

Dimensioned drawings

Installation with a hob.



measurements in mm

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm

